

|--|





	FEMALE FACE V	IEW		
3-POLE	4-POLE	5-POLE		
	WIRING DIAGRA	М		
1 BROWN 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK 5 GREY		

8

7

	MALE FACE VI	EW
3-POLE	4-POLE	5-POLE
4 3	4	4 - + /
• •		
V	VIRING DIAGRAN	1
1 BROWN	1 BROWN	1 BROWN
3 BLUE 4 BLACK	2 WHITE 3 BLUE	2 WHITE 3 BLUE
	4 BLACK	4 BLACK
		5 GREY

CONNECTOR SPECIFICATION:

F

Е

D

С

В

А

10

VOLTAGE RATING	250 VAC/VDC
AMPERAGE RATING	max. 4 AMPS
PROTECTION	IP67
OPERATING TEMPERATURE	-20°C TO 105°C
ASSEMBLY IS	RoHS COMPLIANT

ITEM	COMPONENT	MATERIAL	FINISH
7	LABLE	MYLAR	BLACK/YELLOW
6	0-RING	VITON	RED
5	COUPLER	BRASS	TEFLON/NICKEL
4	SOCKET/PIN CONTACT	COPPER ALLOY	GOLD OVER NICKEL
3	INSERT	PUR	BLACK
2	OVERMOLD	TPE	YELLOW
1	CABLE- #18/3-5 (COPPER STRANDING) 3/4/5 CONDUCT. 300V	JACKET: TPE	JACKET: YELLOW

9

5		<u>_</u>						DIMENS	SION STYLE	SCALE	DESIGN UNITS			
0/02/0		2010/02/03	QUALITY SYMBOLS	/ 1 1 1	ERAL TOLE ES <u>S SPECI</u>				/MM	1:1	METRIC		D ANGLE ECTION	
ION 0317 2010				4 PLACE	 -S+	INCH			DATE 2010/02/01	1	AICRO-CHAN		ΞT	
니는 글	1	2		3 PLACE	S ±	±	CHECK	ED BY	DATE		3/4/5 P. FE 9 8/3-5 YELLOV		F	
DESCRIP WEU2010 STEMMLE				2 PLACE 1 PLAC		<u>±.01</u> ±	RE APPRO	VED BY	2010/02/02 DATE	molex	MOLEX IN			A
	D:NS	Ë		AN AN	IGULAR ±	•	FPAC MATER		2010/02/03		_	JURFURA		4
EC NO.	CHK	APPR			WHERE AP				E SHEET 2		SD-120066-0)21	1 OF 1	
1	10	-	REV		HIN DIMEN		SIZE A3				ORMATION THAT IS			
			5			4			3		2	1		$\overline{\ }$



2

1

F

Е

D

С

В



	10	9	8	7	6	5	4	3	2	1	
F						POL M/ 4	ATERIAL NUMBER EN 1200660545 8	IGINEERING NUMBER 84031K03M080	FINISHED LENG 8.0M +317.5 -0 [26.25'		F
E											E
D											D
C											С
В								DIMENSION STVLE			В
A	10	9	8	7	9 DESCRIPTION EC NO: WEU2010-0317	N:LSTEMMLE 2010/02 D:NS D:NS D:NS D:NS D:NS D:NS D:NS DESCRIPTION DESCRIPRO DESCRIPTION DESCRIPTION D	$\begin{array}{c} \text{CES } \pm & \pm \\ \text{CES } \pm & \pm \\ \text{CES } \pm & \pm .01 \\ \text{CE } \pm 0.3 & \pm \\ \text{ANGULAR } \pm & \\ \text{OULAR } \pm & \\ $		3/4/5 P. FE 18/3-5 YELLO	90/ MA STR N TPE CABLE CORPORATED 021 1 OF 1 PROPRIETARY TO MOLEX	а о. 1

2 1
